## **CHAPTER 8**

## **ADMINISTRATION**

As the saying goes, "No job is complete until the paperwork is done." This holds true for the ABF. Additionally, often you need more information before you can even start a task.

There is no way you can remember every specification, instruction, rule, or requirement. The further you advance, the more you are required to know. The key to not being overwhelmed by this required knowledge is to learn as much as you can, but always know where to get the information you need.

This chapter will cover technical/maintenance manuals, instructions, reports, and logs. We will discuss their purposes, how they are kept current, and where they are found.

### TECHNICAL LIBRARY

A technical publications library serves two important functions. First, it provides a central source of up-to-date information for the use of all personnel in the performance of their work. Second, it is an excellent source of reference information to help in the training of personnel. To perform these functions properly, the library must contain at least one copy of all publications affecting the equipment the division is responsible for.

Typically, the technical library is located in the division office or maintenance office. Management of the library should be assigned to a senior individual who will ensure that all required publications are on board and that all updates and changes are made to the affected publications.

Often, individual workcenters will keep the publications normally used by the workcenter. This is acceptable. However, the technical library manager should maintain a list of all publications held in a workcenter so that those manuals also will receive updates and changes when required. A technical manual used to rebuild a pump is worthless if updated changes are not made and entered on the Record of Changes.

#### TECHNICAL/MAINTENANCE MANUALS

Technical/Maintenance Manuals are the sources of information for guiding naval personnel in the operation and maintenance of all equipment within the Naval Establishment. The manuals are divided into two major types: operational and maintenance.

Operational manuals are publications and other forms of documentation that contain a description of systems and instructions for their effective use. An example of an operational manual is the *Aircraft Refueling NATOPS Manual*, NAVAIR 00-80T-109 (fig. 8-1).

Maintenance manuals are documents containing a description of individual systems for the purpose of




Figure 8-1.—Aircraft Refueling NATOPS Manual.

maintenance and repair. An example of a maintenance manual is the *Technical Manual for Description, Operation, and Maintenance of the JP-5 Jet Fuel Centrifugal Purifier,* NAVSEA S9542-AB-MMO-010 (fig. 8-2).

By proper use of these publications, all equipment can be operated and maintained in the same efficient manner throughout the Navy.

Technical/Maintenance manuals do not contain detailed descriptions or procedures concerning preventive maintenance, since this information is contained on maintenance requirement cards (MRCs). For information on the 3-M System, consult OPNAV-INST 4790.4 (series), *Ship's Maintenance Material Management Manual*.

Technical/Maintenance Manuals do contain the following:

- A description of the equipment
- The theory of operation




Figure 8-2.—JP-5 Centrifugal Purifier Technical Manual.

- Troubleshooting techniques
- Corrective maintenance information
- Specific safety requirements
- · Parts breakdown and numbers
- Sketches, diagrams, and schematics
- · Operating and design limits

Senior petty officers must be able to interpret technical publications and to supervise their use. The senior ABF also must know how to obtain technical publications and how to keep them up-to-date.

Many technical publications issued by the Naval Air Systems Command are of interest to the ABF. The General Information and Servicing section of the Maintenance Instructions Manual for each type of aircraft covers the required procedures for refueling the aircraft. Mobile refuelers and aircraft-handling equipment are covered by other Naval Air Systems Command publications.

Technical publications issued by the Naval Sea Systems Command cover most of the shipboard equipment used by the ABF. The fuel system for each ship is covered in a Ship's Information Book (SIB), The SIB for the ship to which the ABF is attached should be studied thoroughly. Also, each major component is covered by a Technical/Maintenance Manual issued by the Naval Sea Systems Command.

#### INSTRUCTIONS AND NOTICES

The Navy Directives System is used throughout the Navy for the issuance of nontechnical directive-type releases. These directives establish policy, organization, methods, or procedures. They require action to be taken or contain information affecting operations or administration. This system provides a uniform plan for issuing and maintaining directives. Conformance to the system is required of all bureaus, offices, activities, and commands of the Navy. Instructions and Notices are the two types of authorized releases.

Information pertaining to action of a continuing nature is contained in "Instructions." An Instruction has permanent reference value and is effective until the originator supersedes or cancels it. "Notices" contain information pertaining to action of a one-time nature. A Notice does not have permanent reference value and contains provisions for its own cancellation.

For identification and accurate filing, all directives can be recognized by the originator's abbreviation, the type of release (whether an Instruction or a Notice), a subject classification number, and in the case of Instructions only, a consecutive number. Because of their temporary nature, Notices are not assigned consecutive numbers. This information is assigned by the originator and is placed on each page of the directive.

Don't let the word instruction fool you. It may sound like something clerical, but instructions and notices provide us with a tremendous amount of information, and some instructions can be quite large, such as the previously mentioned OPNAVINST 4790.4 (series), *Ships' 3-M Manual* (fig. 8-3).

## MAINTAINING AN ALLOWANCE OF PUBLICATIONS

There are four mandatory requirements to be met in maintaining an allowance of publications (technical and otherwise). These requirements are the following:

• The prescribed publications be on board



Figure 8-3.—Ships' 3-M Manual.

- The publications be maintained up to date
- The publications be ready for immediate use
- · Applicable security provisions be observed

The primary index used to order all Navy technical manuals and forms is the *Navy Stock List of Publications and Forms*. NAVPUBFORMCEN Pub. 2002.

#### MAKING CHANGES TO PUBLICATIONS

Most changes to publications are issued in the form of loose-leaf pages, pen-and-ink changes, or complete revisions. When changes are issued in numbered pages, the old page with the corresponding number is removed and the new replacement page inserted in its place. Specific instructions are normally given with each change on the method to be used in incorporating the change. Changes should be made immediately upon receipt.

A checklist of pages, which are to remain in the publication after the changes have been incorporated, is provided with changes issued for some publications. This checklist should be compared to pages remaining in the publication to ensure they agree. Extra pages are removed and missing pages ordered to bring the publication up-to-date. Obsolete pages removed should be disposed of in accordance with applicable regulations.

When pen-and-ink changes are made, the change number and date should be entered with each change for future reference. Sometimes it is convenient to cut out pen-and-ink changes and insert them in their proper place in a publication by fastening them with transparent tape or glue.

A record sheet is maintained in the front of each publication, indicating the date and number of each change incorporated and the name or initials of the person completing the change. This procedure makes it simple to check if the publication is up-to-date.

## **EQUIPMENT RECORDS AND REPORTS**

Maintaining records and reports is one of the major responsibilities of the senior ABF. All records and reports must be accurate, up-to-date, and according to established standards.

### **Work and Maintenance Logs**

In the work (or operational) logs, hours of operation and operating pressures should be recorded. This information will be very useful in keeping current the

maintenance project cards of the ship. Any other operational data that could be useful at a future date should be recorded. A daily inspection of the fuel system should be made for leaks and other discrepancies and recorded in the log.

The maintenance logbook should contain all work performed on the aviation fuels systems by the repair crews. It should be recorded in a day-to-day order.

Other logbooks required to be kept are the following:

- Fuels security watch log.
- Filter sample/pressure drop log (fig. 8-4).
- Quality surveillance sample log.
- Equipment running logs (fig. 8-5). Each piece of equipment should have its own log, such as service pump #2. transfer pump #1, purifier #3.
- Stripping logs.

All logbooks should be inspected frequently by appropriate petty officers, the work center chief, and the division officer. Often, the information contained in a log may indicate the impending failure of a piece of equipment long before the actual failure occurs.

### **Checklists**

Checklists (fig. 8-6) provide a minimum written list of items for inspection. Checklists are typically

tailored to fit specific equipment or operations and can cover everything from a pre-operational check on a fuel truck to inspecting the entire fuel system after an underway replenishment.

The advantage of using a checklist is obvious. With the items to be inspected written, you are less likely to miss a step or procedure. If you use checklists, make sure all PMS requirements are met.

## **Aircraft Checker Reports**

One of the major problems encountered by senior ABFs in operating an aviation fuels system is keeping accurate records of fuel expenditures. The measuring instruments (meters, liquid-level indicators, sounding tapes) are not sufficiently accurate for use in computing fuel expenditure for a particular aircraft or squadron.

The most accurate way of computing the amount of fuel issued to a particular aircraft is with the use of the aircraft's fuel gages. At the time of arrestment, by subtracting the fuel load from the total capacity of the aircraft's fuel tanks, you can determine how much fuel is needed to top off the tanks. The aircraft's fuel gages are calibrated in pounds of fuel, and a conversion must be made to convert the pounds of fuel issued to gallons.

Fuel checkers are assigned the duty of keeping an account of all fuels issued to or taken from an aircraft.

Checker cards are useful for this purpose. These cards (or sheets) should have places for the date and the checker's name at the top. There should be spaces

		URE DROP LOG			DATE:			•		
ILTERS:	1-2-3-4									
TIME	PRESS	DIFF PRESS	SEPARATORY DIFF PRESS	DIFF PRESS	DISCHARGE PRESS	SAMPLE	VISUAL SAMPLE	RESULT	SERVICE TANK NO.	STGNATURE
										··········
										<del></del>
	<del> </del>									
	<u> </u>					-				
	<u> </u>				-					
						-		<del>  </del>		
	<b> </b>			-						<del></del>
	<b> </b>							<del>  </del>		······································

Figure 8-4.—Example of a fuel sample/pressure drop log.

EA VCCA 1	UN TIME:									
START	STOP	TOTAL	FROM	то	AMOUNT	DUTY FILTER	DEFUEL	VISUAL SAMPLE	LAB SAMPLE	OPERATOR
						20000				
					<del> </del>					
										<del></del>
							ļ			
					<del> </del>		6			
										······································
					1					
										····
								<del>                                     </del>		

Figure 8-5.—Example of an equipment-running log.

on the cards for the squadron number, aircraft side number, the pounds of fuel issued or defueled from the aircraft, the total fuel load, the time of fueling or defueling, and the plane captain's initials. These cards should be turned in to the division petty officer responsible for keeping the fuel expenditure records.

Fire extinguishers (in place, field, operable, curvant inspection tag)  Mozzis storage dust cover and bonding cable on greatly nozzis in security and the place of the place o		item (See paragraph 12.3.3.1)	ОК	Adjust	Repair	REMARKS	_
Current inspection (se)  Quarter inspection (se)  Rotatis elaborate dust cover and bonding cable on greeny nozzie  Probly up nazie to bettom leading adapter or resordation lifeting, and check entire nozzie assembly  Rotation of the state o	-			AOJUST	nopai	- CHIPARO	-
Cable on gravity nozzis   Plots on provisy nozzis   Plots on provisy nozzis   Plots on provision to bottom leading adapter or servication fitting, and check entire nozzis assembly	1	rire extinguishers (in place, filed, operable, current inspection tag)					
searchulation frieng, and check entire nozale assertify	2						
a shreshons and lust saturation  Static bonding cable, plugicip  Leaks (tank, piping, valves, pumps, stc.)  Emergency valves (operation of controls)  Cianniness  Battery, radiator, gas and oil levels  Ughts, reflectors, rearview mirrors  Illiphis, reflectors, rearview mirrors  Static brights and spark arraising mutter  (Eshaust plos arraising mutter  (Eshaust plos	'n	recirculation litting, and check entire nozzle					
5 Leaks (tank, piping, valves, pumps, stc.) 7 Emergency valves (operation of controls) 8 Clanniness 9 Battery, radiator, gas and oil levels 10 Lights, reflectors, rearview mirrors 11 Drain all low point drains (tank, little valves) 12 Enhances from one of controls of the valves of controls of the valves of controls or controls of the valves of controls of the valves of the valv	4	Hose: Check entire length for cuts, cracks, abrasions and fuel saturation					
7 Emergency valves (operation of controls) 8 Cleanliness 9 Batery, radiator, gas and oil levels 10 Lights, reflectors, rearview mirrors 11 Orsin all low point drains (tank, filler/separator, monitor, relevation chamber) 12 (elsak, cradict pas and spark arressing mutter 13 (elsak, cradict pas and spark arressing mutter 14 (elsak, cradict pas and spark arressing mutter 15 Emergency brakes 16 Orsin water from air tanks 17 Pump (noise, overheasing, without passes of the spark of the sp	5	Stalic bonding cable, plug/clip					
8 Clanniness 9 Battery, radiator, gas and oil levels 10 Lights, reflectors, rearrise mirrors 11 Rike/reporator, monitor, relaxation chamber) 12 Enhants pipe and spark arresting muffler (leafe, chade or note) 13 Emergancy brakes 14 Orain water from air tanks 15 Fill hose with full pump pressure and check 16 Open notatio valve, chack nose seal for leaks, 16 Open notatio valve, chack nose seal for leaks, 17 Pump (noise, overheating), volvation) 18 Orain water, sold and dools and record results 19 Rocord pressure differential reading from 20 Rocord pressure differential reading from 20 Rocord pressure differential reading from 20 Rocord pressure d	6	Leaks (tank, piping, valves, pumps, etc.)					
9 Battery, radiator, gas and oil levels 10 Lights, reflectors, rearview mirrors 11 Drian all low point drains (Jank, Riterisparator, monitor, relaxation chamber) 12 Eshaust pipe and spark arresting multiler (eds., cracks or notes) 13 Emergency brakes 14 Drain water from air tanks 15 Fill hose with full pump pressure and check enlire system for leaks criculate tubul, and check flow rate (criculate fluid, and check flow rate) 16 Open nozzle valve, check nose seal for leaks, criculate fluid, and check flow rate (criculate fluid, and check flow rate) 17 Pump (noties, overheating, vibration) 18 Draw nozzle sample, visually inspect for water, solide and oboler and record results 19 Record gressure differential reading from (Pump Pressu, Filier-Prass, Diff, filier/leser/ard and monitor) 19 Record gressure differential reading from (Pump Pressu, Filier-Prass, Diff, filier/leser/ard and monitor) 10 Draw flower filier-prass Diff, filier/leser/ard and monitor (Pump Pump R.P.M. Monitor Press, Diff.	7	Emergency valves (operation of controls)					
10 Lights, reflectors, rearview mirrors 11 Drain all low pour drains (Link, liker/resparator, monitor, relazation chamber) 12 Eshaust pipe and spark arresting multier 13 Emergency brakes 14 Drain water from air tanks 15 Fill hose with full pump pressure and check entire system for leaks, circulate turn, and check flow can be considered to the circulate turn, and check flow can be considered to the circulate turn, and check flow can be considered to the circulate turn, and check flow can be considered to the circulate turn, and check flow can be considered to the circulate turn, and check flow can be considered to the circulate turn, and check flow can be considered to the circulate turn, and check flow considered to the circulate turn, and check flow considered to the circulate turn of the circulate tur	8	Cleanliness					
17 Drain all low point drains (tank, little	9	Battery, radiator, gas and oil levels					
Bitter/separator, monitor, relevation chamber)	10	Lights, reflectors, rearview mirrors					
(elast, cracks or noise)	11	Drain all low point drains (tank, filter/separator, monitor, relaxation chamber)					
14 Drain water from air tanks 15 Fill hose with full pump pressure and check entire system for lasks 16 Open nogzie valve, check hose seal for leaks, circulate fuel, and check floor rate 17 Pump (noise, overheating, withoston) 18 Drav nozzie sample, visually inspect for water, solids and dozie and record results 19 Record gressure differential reading from 19 Pump R.P.M. Ministry D.H.	12	Exhaust pipe and spark arresting mulfler (leaks, cracks or noise)					
Fill hose with full pump pressure and check	13	Emergency brakes					
Copen nozzle valve, check nose seal for leaks,   Copen nozzle sample, visually inspect for   Water   Cobr	14	Drain water from air tanks					
Pump (noise, overheating, whreaton)	15	Fill hose with full pump pressure and check entire system for leaks					
18 Draw nozzie sample, visually inspect for water, solids and color and record results Color Seisment Color Seisment I Paccod pressure differential reading from Pump Pressu, Filter Press, Diff, filter/search and monitor Press, Diff, Monitor	16						
water, solids and color and record results  Color  Pump Pressu. Filter Press, Diff.  Filter-payater and monitor Pump R.P.M. Monitor Press, Diff.	17	Pump (noise, overheating, vibration)					_
filter/separator and monitor Pump R.P.M. Monitor Press, Diff.	18		Color		Sediment	_	
Flow Rate	19		Pump Pressu. Pump R.P.M. Flow Rate			Filter Press. Diff. Monitor Press. Diff.	

Figure 8-6.—Example of a daily aircraft refueling equipment checklist.

They are used in filling out squadron requisitions. In case of an aircraft accident, the cards should be removed from use and filed for future use in the accident investigation, if required. These cards are also used in accounting for the amount of fuel on board the ship.

The fuel checker cards are used in conjunction with the daily pumproom reports to establish the amount of fuel delivered and the amount of fuel remaining on board daily. The cards are used to compute the amount of fuel used by each squadron. A supply requisition is sent to each squadron for payment for the amount of fuel used. The cost of the fuel is paid for out of that squadron's operation and line maintenance of aircraft allotment.

### **Sounding Report**

Another report required in V-4 Division is the daily sounding report. This is a two-copy report; one copy is submitted to the engineering log room, and the other copy is retained in V-4 division files. The daily sounding report contains tank numbers, capacity (in gallons and in feet and inches), the previous day's soundings, the present soundings, and the percentage of fuel on board.

### **Daily Fuel Reports**

The daily fuel report is compiled from the aircraft checker cards, the pumproom reports, and tank sounding reports. This report shows the total amount of fuel on board. It is normally signed by the V-4 division officer and submitted to each of the following officers:

- Commanding officer
- Air officer
- Engineering officer
- Operations officer
- Officer of the deck
- Supply officer

### **CASUALTY REPORTING**

The casualty report (CASREP) has been designed to support the Chief of Naval Operations (CNO) and fleet commanders in the management of assigned forces. The effective use and support of Navy forces require an up-to-date, accurate operational status for each unit. An important part of operational status is casualty information. The reporting of casualties results in operational commanders and support personnel being advised of the status of significant equipment malfunctions that could result in the degradation of a unit's readiness. The CASREP also reports the unit's need for technical assistance and/or replacement parts to correct the casualty.

A *casualty* is defined as an equipment malfunction or deficiency that cannot be corrected within 48 hours that

- reduces the unit's ability to perform a primary mission, or
- reduces the unit's ability to perform a secondary mission, or
- reduces a training command's ability to perform its mission, or a significant segment of its mission, and cannot be corrected or adequately accommodated by rescheduling or doubleshifting lessons or classes.

The CASREP system contains four types of reports: initial, update, correct, and cancel. These reports are described in general in the following paragraphs. For more complete information on preparation and submission of the reports, see *Operational Reports*. NWP 10-1-10. (Formerly NWP 7, Revision A.)

# **Initial Casualty Report** (Initial)

An Initial casualty report identifies the status of the casualty and any parts and/or assistance that is needed. Operational and staff authorities use this information to set priorities for the use of resources.

## **Update Casualty Report** (**Update**)

An Update casualty report contains information similar to that submitted in the Initial report and/or submits changes to previously submitted information.

## **Correction Casualty Report** (Correct)

A unit submits a correction Correct casualty report when equipment that has been the subject of casualty reporting is repaired and back in operational condition.

## **Cancellation Casualty Report** (Cancel)

A unit submits a cancellation Cancel casualty report when equipment that has been the subject of casualty reporting is scheduled to be repaired during an overhaul or other scheduled availability. Outstanding casualties that will not be repaired during such availability will not be canceled, and will be subject to normal follow-up casualty reporting procedures as specified.

### **SURVEYS**

The purpose of surveys is to determine the reasons and/or responsibilities for the loss, damage, or destruction of Government material and to determine the actual loss to the U.S. Government. Immediately upon the discovery of the loss, damage, or destruction of Government material, a preliminary investigation is conducted. The investigation is conducted to determine if there is evidence of negligence, willful misconduct, or deliberate unauthorized use. This preliminary investigation is conducted by the department head or division officer (or equivalent) responsible for the material. When circumstances warrant, such as an indication of criminal action or gross negligence, the CO or OIC may appoint a surveying officer or a survey board to investigate the situation further. However, individuals who are accountable or responsible for the material in question may not be appointed as a surveying officer.

An investigation or a review must determine what caused the loss, damage, or destruction of the material being surveyed. The facts surrounding the incident must be thoroughly and quickly investigated to determine the cause. However, the investigation or review should not be limited to the verification of statements from individuals. The investigation should be broad enough to ensure that the interests of the Government, as well as the rights of the individual(s) and the Navy activity, are fully protected. A review is required to prove or refute statements from individuals and to place the responsibility where it belongs.

Research action is not required when the CO or OIC believes that negligence was not involved in the loss, damage, or destruction of Government property. When, for reasons known to the CO or OIC, negligence or responsibility cannot be determined and for those reasons research would be an unnecessary administrative burden, research action is not required. Research action is not usually required when an individual accepts responsibility for the loss, damage, or

destruction of property and voluntarily offers to reimburse the Government for the material.

There are many situations that may require a survey, but the ABF is concerned mainly with bulk petroleum products. If a loss exceeds stated allowances (for example, MOGAS – one half of one percent; JP-5 – one quarter of one percent), a survey is required. If the cause of the loss is unresolved, a DD Form 200, Report of Survey, will be initiated.

More detailed information is available in NAV-SUP Pub. 485, *Afloat Supply Procedures*.

#### **SUMMARY**

There is no possible way every instruction or manual you will be required to use can be covered here. As systems and equipment are tailored for each command, so too are the publications required to support the command. As was stated earlier, you may not know a specific detail of an operation or maintenance, but you should know where to get the information. Learn to use your instructions, technical manuals, and other publications early in your career. You can 't go wrong.